

CSK head, TX, yellow zinc-plated



BUILDING MATERIALS

- Glued-laminated timber
- Cross-laminated timber
- Laminated veneer plywood panels (e.g. Multiplex)
- Hard woods (pre-drilled)
- Chipboards and oriented strand boards (e.g. OSB panels)
- Plywood
- Solid wood panels
- Soft woods
- And many other wood materials

APPROVALS



ADVANTAGES/BENEFITS

- The unique Power-Fast thread reaches into the screw tip and ensures a fast bite. This makes your work noticeably easier with all wood materials.
- The shank ribs (for screws with partial thread from 50 mm in length and up) substantially reduce drive-in resistance and thus enable greater power and battery conservation in your work.
- The optimised head geometry enables an exact and splinter-free surface finish without the screw twisting off, even with connections close to the edge.
- The ETA approval guarantees the high safety standard and the premium quality of fischer Power-Fast screws.

APPLICATIONS

- General wood joints
- Finger tightening elements
- Safety-relevant applications
- Plankings
- Skirting
- Door and metal fittings

APPLICATIONS

- General wood joints
- Finger tightening elements
- Safety-relevant applications
- Plankings
- Skirting
- Door and metal fittings

TECHNICAL DATA



fischer Power-Fast-Box

Article name	Art.-No.	Contents
FAB FPF ST YZ 245 P	667005	245 Power-Fast screws, Ø 3,5 to Ø 5, 1 bit TX 10, 1 bit TX 20